

www.tripplite.com



8 Right-Angle Outlet Vertical Power Strip, 120V, 15A, 15-ft. Cord, 5-15P, 24 in.

MODEL NUMBER: PS2408RA









The PS2408RA power strip provides horizontal or vertical power distribution for rack-mount, raceway and workbench applications in a convenient 24-inch mountable housing.

Description

The PS2408RA provides a 15-amp, 120v power strip with 8 right-angle NEMA 5-15R receptacles in a rugged, all-metal, mountable housing. It allows for both vertical and horizontal mounting, making it ideal for a variety of uses including office, rack-mount, workbench, industrial and telecom applications. With a right angle NEMA 5-15P plug and 15-ft. power cord, you don't have to install the PS2408RA next to outlets you already have; it can be mounted across the room and deliver reliable service where you need it most. A lighted and covered On/Off switch helps prevent accidental shut-offs, while a 15-amp circuit breaker guards against dangerous circuit overloads. Its sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory or factory environments.

Features

Multi-Outlet Power Distribution

Vertical or Horizontal Moun

Extra Long Power Cord

Premium Safety Features

Heavy-Duty Housing

Specifications

Highlights

- Ideal for applications needing multiple convenience outlets for powering a variety of electronic equipment
- 24-in mountable housing with 8 right-angle NEMA 5-15R receptacles, right-angle plug and a 15 ft. power cord
- Lighted, covered On/Off switch and 15-amp circuit breaker
- Sturdy construction and heavyduty, all-metal housing

Package Includes

- PS2408RA Power Strip
- Mounting hardware
- Instruction manual



OVERVIEW		
UPC Code	037332187451	
OUTPUT		
Frequency Compatibility	60 Hz	
Output Receptacles	(8) 5-15R	
Output (Watts)	1800	
Circuit Breaker (amps)	15	
	2.48 in.	
Outlet Spacing	Yes	
Right-Angle Outlets	res	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A 120V	
Input Connection Type	Right Angle Nema 5-15P	
Input Plug Features	Black	
Input Cord Length (ft.)	15	
Input Cord Length (m)	4.57	
Input Cord Gauge Type	14/3 SJT	
Voltage Compatibility (VAC)	120	
USER INTERFACE, ALERTS & CONTROLS		
Switches	Lighted 2 position switch controls power to all outlets	
Locking Switch Cover	Transparent on/off switch cover prevents accidental turn-off	
PHYSICAL		
Shipping Dimensions (hwd / in.)	2.40 x 4.61 x 28.19	
Shipping Dimensions (hwd / cm)	6.10 x 11.71 x 71.60	
Shipping Weight (lbs.)	3.14	
Shipping Weight (kg)	1.42	
Unit Dimensions (hwd / in.)	1.25 x 1.68 x 24.52	
Unit Dimensions (hwd / cm)	3.18 x 4.27 x 62.29	
Unit Weight (lbs.)	2.71	
Unit Weight (kg)	1.23	
Material of Construction	Aluminum	
Included Mounting Accessories	Includes mounting clips	



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Receptacle Color	Black	
Color (AC Line Cord)	Black	
Form Factors Supported	Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications	
Outlets Measurement (Center to Center)	63mm	
CERTIFICATIONS		
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies